

CARE FOR CLARITY



Application Expertise Included



The new automatic filter aquaBoll®



The challenge: Flexibility, efficiency and adaptability

As the technology leader in industrial filtration, BOLL & KIRCH always strives for innovative and sustainable filtration solutions. This guiding principle is the basis for the realisation of a new concept for fully automatic water filtration. The aquaBoll[®] automatic filter series significantly increases the overall plant efficiency of your specific application through optimised functionality and novel adaptability.



A revolution in water filtration

aquaBoll®

Individual platform concept $\ igodot$

Minimal operating costs $\ igodot$

The solution: A failsafe platform concept

The individuality and performance of the aquaBoll® filter is based on a novel platform concept, which is realised by a multi-part housing with wide adaptive possibilities - and all that in the smallest space. Filter

elements, variable connection-flange positions as well as different housing materials are essential components for optimal adaptation of the automatic filter for your specific filtration requirements.

Welded housings in three versions

- ⊘ Adaptive filtration configurations
- \bigcirc Multi-part housing construction
- ⊘ Various housing materials and interior coatings
- ⊘ Flexible positioning of connection flanges
- ⊘ High flow rates in minimum installation space





- ⊘ Adaptive filtration configurations
- ⊘ Multi-part housing construction
- ⊘ Various housing materials and interior coatings
- ⊘ High flow rates in minimum installation space
- ⊘ Wide range of housing sizes -DN 50 to DN 900





Delivers clarity: aquaBoll® in your specific application

The aquaBoll[®] automatic filter is especially capable of handling demanding situations and the toughest conditions. Complex filtration processes can be mastered in every application by the special properties and functions. The standardised multiple platform concept ensures low acquisition costs and high flexibility. The compact design allows easy access to all relevant components. Thus, commissioning and maintenance expenses are reduced considerably. Service speeds are significantly improved due to easy access and increased availability of standardised components. The combination of innovative design, high-quality components and



a long service life allows for a cross-sectoral approach. This leads to a sustainable increase in water quality. The aquaBoll[®] is thus able to meet the requirements of a wide range of industries with unprecedented efficiency.





Standardised components

Innovative backflushing technology

The priority: Optimum protection of your application

The aquaBoll[®] ensures the protection of the actual application with a consistently high filtration quality and failure safety. Standardised and high-quality components lay the foundation for this. The



Platform-based housing concept


The rotative adjustability of the housing components allows positioning of the connection flanges to suit your system. Housing and coating materials are individually configurable.



Fully automatic backflushing technology

The filtration process takes place continuously and without interruption thanks to our fully automatic backflushing technology. Parallel to the filtration process, backflushing takes place either controlled by differential pressure or by programmable time intervals.

optimised operation with fully automatic backflushing technology keeps running costs low. Failures and malfunctions of your application are a thing of the past.



High flow rates at maximum variability

The high individuality of aquaBoll[®] is provided by the novel platform concept, which is based on a multi-part housing with wide adaptation possibilities. This allows the highest flow rates in the smallest possible space.

Reliability through quality

Technical specifications: Our know-how sets high standard

Three concepts of adaptive filtration elements are available to optimise the filtration conditions: filter candle, sieve cylinder and fine sieve cylinder. Depending on the size, the required filtration efficiency and the degree of contamination of the process water, these are interchangeable and adaptable. Special conditions may require special profiles that can be included in the adaptive elements, thus covering all applications.

⊘ Flexible filtration concepts

Maximum adaptability



Fine sieve cylinder element

fineness 10 µm - 80 µm nominal diameter connection flanges DN 50 - DN 500 (2" - 20") housing diameter

273 mm - 750 mm



Filter candle element

fineness 100 µm - 1 mm nominal diameter connection flanges DN 50 - DN 1000 (2" - 40") housing diameter 273 mm - 1350 mm

Flexibility and precision for best results in filtration



Sieve cylinder element

fineness

2 mm, 3 mm and 5 mm nominal diameter connection flanges DN 50 - DN 500 (2'' - 20'') housing diameter 273 mm - 750 mm





The premium products of BOLL & KIRCH are setting the benchmark in the field of cleaning process fluids. Our constant and continuous engineering guarantees self-cleaning solutions in filtration to increase the overall efficiency of your application to a new level.

- Improved cleaning result
- Effective plant protection
- Considerable cost reduction

Regarding the realisation of application-oriented solutions, our customers rely on the flexibility of our processes and appreciate personal consulting and reliable service.

Contact:

Boll & Kirch Filterbau GmbH Siemensstraße 10 – 14 50170 Kerper Telephone: +49 2273 562 0 Fax: +49 2273 562 223 Email: info@bollfilter.de www.bollfilter.com

